



玄茂科技股份有限公司
 HSUAN MAO TECHNOLOGY CO., LTD.

UNIT

SHEET

SCALE

PART NAME

MM

2-1

4:1

FPC/FFC P:2.54 NON-ZIF
TOP ENTRY SINGLE CONTACT

APPD.

CKD.

TOLERANCE

PART NO.

REV.

制表日: 2000/06/07

DRAWING.

APPROVED

Helwin

T.J.A

± 0.5

C3900-XXSTTB00

A

■ MATERIAL

INSULATOR: GLASS-REINFORCED THERMOPLASTIC.
 CONTACT: PHOSPHOR BRONZE.
 PLATING: TIN PLATED OVER NICKEL.

■ SPECIFICATION

VOLTAGE RATING: 250 VAC RMS.
 CURRENT RATING: 1 AMP.
 DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC RMS 60 Hz.
 FOR 1 MINUTE.
 INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.
 CONTACT RESISTANCE: 25 MILLIOHMS MAX.
 DURABILITY: 20 CYCLES.

■ ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C.

Circuit	Dimension			Circuit	Dimension		
	A	B	C		A	B	C
2	2.54	7.76	9.87	15	35.56	40.78	42.89
3	5.08	10.30	12.41	16	38.10	43.32	45.43
4	7.62	12.84	14.95	17	40.64	45.86	47.97
5	10.16	15.38	17.49	18	43.18	48.40	50.51
6	12.70	17.92	20.03	19	45.72	50.94	53.05
7	15.24	20.46	22.57	20	48.26	53.48	55.59
8	17.78	23.00	25.11	21	50.80	56.02	58.13
9	20.32	25.54	27.65	22	53.34	58.56	60.67
10	22.86	28.08	30.19	23	55.88	61.10	63.21
11	25.40	30.62	32.73	24	58.42	63.64	65.75
12	27.94	33.16	35.27	25	60.96	66.18	68.29
13	30.48	35.70	37.81	26	63.50	68.72	70.83
14	33.02	38.24	40.35	27	66.04	71.26	73.37

玄茂科技股份有限公司
 HSUAN MAO TECHNOLOGY CO., LTD.

UNIT SHEET SCALE PART NAME

MM 2-2 4:1 FPC/FFC P:2.54 NON-ZIF
 TOP ENTRY SINGLE CONTACT

APPD. CKD. TOLERANCE PART NO. REV.

制表日: 2000/06/07

DRAWING. APPROVED

Helwin *J.J.A*

± 0.5 C3900-XXSTTB00 A