



MATERIAL: NYLON66 UL94V-2
 VOLTAGE RATING: AC/250V, DC/350V
 CURRENT RATING: AC, DC, 15A
 INSULATION RESISTANCE: $\geq 1.000M \Omega \cdot \text{MIN.}$
 WITHSTAND VOLTAGE: $\geq 1.500V \text{ AC/MINUTE}$
 TEMPERATURE RANGE: $-25^{\circ}\text{C TO } +85^{\circ}\text{C}$

DIMENSION: (MM)

P: 6.3 ± 0.1
 L: 13.5 ± 0.2
 W: 6.3 ± 0.2
 H: 25.6 ± 0.3

| | | | | |
|------------------------|--|----------------|-------------------|--------------------------------|
| APPD. 核准 Angel | | | TOLERANCE 容許公差 | PART NAME 品名 |
| DWG. 製圖 Yumi | | | SCALE 比例 參考 | |
| DATE 制表日 2010/03/31 | | UNIT 單位 M M | SIZE 紙張尺寸 A 4 | PART NO. 料號 H2130-02PSNW00R |
| PAGE 張數 1 OF 1 | | REV. 版次 A | | |

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.

$\phi 2.36\text{mm}$ MALE HOUSING 1X2P W/O LOCKING
 RIBS W/O EAR WHITE COLOR ROHS LOW LEAD