



Approval	 	
Capability	UL	IEC
Standard	600V	800V
Rated Voltage	20A	24A
Rated Current	Wire size	0.2-2.5mm ²
Wire size	24-12AWG	
T/W/End plate	6.2/42.5/1.5mm	
Height(mm)(NS35:7.5/NS35:15/NS32)	42/49.5/47mm	
Rated surge voltage/Contamination Class	8KV/3	
Stripping length	7mm	
Screw thread/Tightening torque	M3/0.5N.m/4.5Lb-in	
Internal cylindrical gage	A3	
Insulating Material/Inflammability class	PA/V-0	
Specification	Model	Pieces
(1) Terminal block	PC 2.5B	50
(2) End cover	D-PC 1.5	50
(3) Fixed bridge	FBI 2-6	10
2-P	FBI 3-6	10
3-P	FBI 5-6	10
5-P	FBI 10-6	10
10-P		
(4) Step bracket		
(5) Insertion bridge	EB 2-6	100
2-P	EB 3-6	100
3-P	EB 10-6	10
10-P		
(6) Isolator bridge bar, 10P	ISSBI 10-6	10
(7) Bridge bar isolator	IS-K 4	100
(8) Switching bridge	USBR 2-7	1
(9) Separating plate	TS-KK 3	100
(10) Separating plate, width 1.5mm	ATP-PC	50
(11) Test plug socket	DSB 3/10/4	100
(12) Test plug socket insulated	DSBJ 3/13/4	100
(13) Zack strip	ZB6	

HOW TO ORDER :

- **P** - -

X	X	X
---	---	---

Customer Request

Series No.

No. of pole

Color

1	Gray	4	Green	7	Transp-arent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	white

 mm (INCH)	 DEGSON ELECTRONICS CO., LTD.
 THROUGHT LINE PROJECTION	NAME PC 2.5B