



SPECIFICATIONS

Current rating : 2A AC,DC
 Voltage rating : 250V AC,DC
 Temperature range : -25°C to +85 °C
 Contact resistance : 20mΩ Max.
 Insulation resistance : 1000MΩ Min.
 Withstanding voltage : 800V AC/minute
 Material : Nylon 66, UL94V-0

Ordering Information & Dimensions

Poles	Dimension (mm)	
	A	B
2x2	2.00	5.90
2x3	4.00	7.90
2x4	6.00	9.90
2x5	8.00	11.90
2x6	10.00	13.90
2x7	12.00	15.90
2x8	14.00	17.90
2x9	16.00	19.90
2x10	18.00	21.90
2x11	20.00	23.90
2x12	22.00	25.90
2x13	24.00	27.90
2x14	26.00	29.90
2x15	28.00	31.90
2x16	30.00	33.90
2x17	32.00	35.90
2x20	38.00	41.90

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差 0 ±0.3 .00 ±0.2 ANG ±	PART NAME 品名 2.0mm HOUSING 2X??P WHITE COLOR ROHS LOW-LEAD
DWG. 製圖 HELEN	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 H2003-XXPDW000R
DATE 制表日 2009/2/16	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A4	REV. 版本 A