



Approval	 	
Capability	UL	IEC
Standard	600V	500V
Rated Voltage	10A	17.5A
Rated Current	26-16AWG	0.2-1.5mm ²
Wire size	4.2/42.5/1.5mm	
T/W/End plate	42/49.5/47mm	
Height(mm)(NS35:7.5/NS35:15/NS32)	6KV/3	
Rated surge voltage/Contamination Class	7mm	
Stripping length	M2/0.2N.m/1.73Lb-in	
Screw thread/Tightening torque	A1	
Internal cylindrical gage	PA/V-0	
Insulating Material/Inflammability class	Model	Pieces
(1) Terminal block	PC 1.5	50
(2) End cover	D-PC 1.5	50
(3) Fixed bridge	FBR1 10-4	10
(4) Step bracket		
(5) Insertion bridge		
(6) Isolator bridge bar, 10P		
(7) Bridge bar isolator		
(8) Switching bridge		
(9) Separating plate		
(10) Separating plate, width 1.5mm	ATP-PC	50
(11) Test plug socket		
(12) Test plug socket insulated		
(13) Zack strip	ZB4	

HOW TO ORDER :

- **P** - -

X	X	X
Customer Request		

Series No. **No. of pole** **Color**

1	Gray	4	Green	7	Transp-arent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	white

 mm (INCH)	 DEGSON ELECTRONICS CO., LTD.
 THROUGHPHOLE PROJECTION	NAME PC 1.5